

Product Specifications For 336



Engine

Net Power - ISO 9249	223.5 kW
Net Power - ISO 9249 (DIN)	304 hp (metric)
Engine Model	Cat C7.1 TTA
Engine Power - ISO 14396	225 kW
Engine Power - ISO 14396 (DIN)	306 hp (metric)
Bore	105 mm
Stroke	135 mm
Displacement	7.01 l
Biodiesel Capability	Up to B20 ¹
Emissions	Meets U.S. EPA Tier 4 Final, EU Stage V, and Japan 2014 emission standards.
Note (1)	Net power advertised is the power available at the flywheel when the engine is equipped with fan, air intake system, exhaust system, and alternator with engine speed at 2,000 rpm. Advertised power is tested per the specified standard in effect at the time of manufacture.

Note (2)

¹Cat diesel engines are required to use ULSD (ultra-low sulfur diesel fuel with 15 ppm of sulfur or less) and are compatible* with ULSD blended with the following lower-carbon intensity fuels** up to: 20% biodiesel FAME (fatty acid methyl ester)*** 100% renewable diesel, HVO (hydrotreated vegetable oil) and GTL (gas-to-liquid) fuels Refer to guidelines for successful application. Please consult your Cat dealer or “Caterpillar Machine Fluids Recommendations” (SEBU6250) for details. *While Caterpillar engines are compatible with these alternative fuels, some regions may not allow their use. ** Tailpipe greenhouse gas emissions from lower-carbon intensity fuels are essentially the same as traditional fuels. *** Engines with no aftertreatment devices are compatible with higher blends, up to 100% biodiesel (for use of blends higher than 20% biodiesel, consult your Cat dealer).

Weights

Operating Weight	36800 kg
------------------	----------

Working Ranges And Forces

Maximum Digging Depth	8210 mm
Boom	Reach 6.5 m (21'4")
Stick	Reach 3.9 m (12'10")
Bucket	HD 2.00 m³ (2.61 yd³)
Maximum Reach at Ground Level	11760 mm
Maximum Cutting Height	10740 mm
Maximum Loading Height	7470 mm
Minimum Loading Height	1890 mm
Maximum Depth Cut for 2440 mm (8 ft) Level Bottom	8080 mm
Maximum Vertical Wall Digging Depth	6490 mm
Bucket Digging Force - ISO	210 kN
Stick Digging Force - ISO	144 kN

Hydraulic System

Main System - Maximum Flow	560 L/min
Maximum Pressure - Equipment	35000 kPa
Maximum Pressure - Equipment - Lift Mode	38000 kPa
Maximum Pressure - Travel	35000 kPa
Maximum Pressure - Swing	29400 kPa

Swing Mechanism

Maximum Swing Torque	143 kN·m
----------------------	----------

Note (1)

*For CE-marked machine default value may be set lower

Service Refill Capacities

Fuel Tank Capacity	600 l
Cooling System	39 l
Engine Oil	25 l
Swing Drive - Each	18 l
Final Drive - Each	8 l
Hydraulic System - Including Tank	373 l
Hydraulic Tank	161 l
DEF Tank	50 l

Dimensions

Boom	Reach 6.5 m (21'4")
------	---------------------

Stick	Reach 3.9 m (12'10")
Bucket	HD 2.00 m³ (2.61 yd³)
Shipping Height - Top of Cab	3180 mm
Handrail Height	3180 mm
Shipping Length	11180 mm
Tail Swing Radius	3530 mm
Counterweight Clearance	1260 mm
Ground Clearance	510 mm
Track Length	5030 mm
Track Length to Center of Rollers	4040 mm
Track Gauge	2740 mm
Transport Width	3190 mm
Transport Width - 850 mm (33") Shoes	3590 mm

Sustainability

Recyclability	98%
----------------------	-----

Air Conditioning System

Air Conditioning	The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a or R1234yf. See the label or instruction manual for identification of the gas. If equipped with R134a (Global Warming Potential = 1430), the system contains 0.90 kg (1.984 lb) of refrigerant, which has a CO2 equivalent of 1.287 metric tonnes (1.419 tons). If equipped with R1234yf (Global Warming Potential = 0.501), the system contains 0.780 kg (1.719 lb) of refrigerant, which has a CO2 equivalent of 0.001 metric tonnes (0.001 tons).
-------------------------	--

336 Standard Equipment

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

CAT TECHNOLOGY

VisionLink™

Remote Flash

Remote Troubleshoot

Operator Coaching

Compatibility with radios and base stations from Trimble, Topcon, and Leica

Capability with 3D grade systems from Trimble, Topcon, and Leica

Cat Grade with 2D

Cat Assist (Grade, Boom, Bucket, Swing, Lift)

Cat Payload (On-the-go weighing, Semiautomatic calibration, Payload/cycle information, USB Reporting Capability)

Work tool recognition and tracking (Requires PL161 attachment locator on work tool and Bluetooth receiver on machine)

ELECTRICAL SYSTEM

Maintenance-free 1,000 CCA batteries (x2)

Centralized electrical disconnect switch

LED exterior chassis and boom lights

ENGINE

Three selectable modes: Power, Smart, Eco

Auto engine speed control

- 18° C (0° F) cold start capability

Double element air filter with integrated pre-cleaner

Remote disable

HYDRAULIC SYSTEM

Boom and stick regeneration circuit

Electronic main control valve

Auto heavy lift

Auto dig boost

Auto hydraulic oil warmup

Bio hydraulic oil capability

Reverse swing damping valve

Auto swing parking brake

High performance hydraulic return filter

Two speed travel

SAFETY AND SECURITY

Cat E-Fence

Auto hammer stop

Lockable door, fuel, and hydraulic tank locks
Lockable fuel drain compartment
Service platform with anti-skid plate & recessed bolts
RH handrail and handhold
Signaling / warning horn
Ground-level secondary engine shutoff switch
Rearview camera
Lockable disconnect switch

SERVICE AND MAINTENANCE

Integrated vehicle health management system
Grouped location of engine oil & fuel filters

UNDERCARRIAGE AND STRUCTURES

Towing eye on base frame
Swivel guard
HD bottom guard
HD travel motor guards
Grease lubricated track

DELUXE CAB

High-resolution 203 mm (8") LCD touchscreen monitor
Auto bi-level air conditioner
Jog dial and shortcut keys for monitor control
Keyless push-to-start engine control
Height-adjustable console
Tilt-up left-side console
Heated air-suspension seat
Monitor integrated Bluetooth radio with USB/Aux ports
12V DC outlets
Document storage
Overhead storage and rear storage with nets
Cup holder
Openable two-piece front window
Rear window emergency exit
Radial wiper with washer
Openable polycarbonate skylight hatch
LED dome light
Floor welcome light
Roof sunscreen
Roller front sunscreen
Washable floor mat
Beacon ready

PREMIUM CAB

High-resolution 254 mm (10") LCD touchscreen monitor

Auto bi-level air conditioner
Jog dial and shortcut keys for monitor control
Keyless push-to-start engine control
Height-adjustable console
Tilt-up left-side console
Heated and ventilated air-suspension seat
Monitor integrated Bluetooth radio with USB/Aux ports
12V DC outlets
Document storage
Overhead storage and rear storage with nets
Cup holder
Openable two-piece front window
Rear window emergency exit
Parallel wiper
Openable polycarbonate skylight hatch
LED dome light
Floor welcome light
Roof sunscreen
Roller front sunscreen
Washable floor mat
Beacon ready

336 Optional Equipment

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

BOOMS AND STICKS

6.18 m (20'3") Mass boom
6.5 m (21'4") Reach boom
2.55 m (8'4") Mass stick
2.8 m (9'2") Reach stick
3.2 m (10'6") Reach stick
3.9 m (12'10") Reach stick
TB family bucket linkage with/without lifting eye
DB family bucket linkage with/without lifting eye

CAT TECHNOLOGY

VisionLink™ back office reporting
Cat Grade Connectivity
Cat Grade 2D with Attachment Ready Option (ARO)
Cat Grade with 3D (single or dual GNSS)
Cat Grade 3D Ready
GNSS antennae
Laser catcher
Cat Tilt Rotator (TRS) Integration
Operator Coaching

Advanced Payload (Daily totals, Custom lists, Smart weight target, E-ticket Integration)

ELECTRICAL SYSTEM

Maintenance-free 1,000 CCA batteries (x4)

ENGINE

Cold start block heater

52° C (126° F) high-ambient cooling

Hydraulic reverse fan

-32° C (-25° F) cold start capability

HYDRAULIC SYSTEM

Single one-way circuit

Combined two-way circuit

Hydraulic efficiency monitoring

SAFETY AND SECURITY

Cat Command (remote control)

Swing alarm

Boom lowering check valve

Stick lowering check valve

UNDERCARRIAGE AND STRUCTURES

Full-length track guiding guards

Segmented two-piece track guiding guards

HD rollers

HD swing frame

HD swing bearing

6.8 mt (14,991 lb) counterweight

7.56 mt (16,667 lb) counterweight

600 mm (24") double grouser, triple grouser, HD triple grouser track shoes

700 mm (28") triple grouser track shoes

800 mm (31") triple grouser track shoes

850 mm (33") triple grouser track shoes

DELUXE CAB

High-resolution 254 mm (10") LCD touchscreen monitor

Roller rear sunscreen

Cat Stick Steer

Auxiliary relay

PREMIUM CAB

One-piece front windshield

Cat Stick Steer

Auxiliary relay